


MAC 1000/1300



For reeled flexible round
and flat cables



MAC1000 is designed to dereel flexible round or flat cables and feed cutting machines or cut / strip machines. Continuous cable adjustment is achieved by the pulleys through which the cable passes.

This system prepares a cable reserve for cut / strip machines and cutting machines, and automatically adjusts the machine's parameters.


The MAC1000 dereeler is independent and dereels the cable only when it is pulled by cut / strip machines or cutting machines. When it is connected to the cut / strip machine, both machines must be set to START to begin cable processing. Movement transmission is achieved through an automatic braking gear motor which stops the coil in case of an emergency or if the doors of the dereeler are opened. The entire unit is mounted on swiveling wheels to facilitate the insertion of the reel, and contains a mechanical system to raise the reel.

A safety device mounted on the first pulley halts the machine in case of emergency, if the cable is not dereeling correctly. The unit is cased in perforated metal screen which protects the operator from all moving parts yet allows constantly visibility of the job at hand.

Manufactured using high quality methods and materials, the machine guarantees long term durability. All mechanical details are treated to prevent environmental oxidation.

The mechanical movement components are assembled on bearings and the sliding shafts are ground, hardened and mounted on bushings.

Electronic parts are produced with reliability and functionality in mind, using high integration components, while the top quality pneumatic parts can be easily found in Europe and abroad. The electrical system conforms to EN60204-1 industry regulations.



EN / 10-2018 / Rev. 00

SAMEC MACCHINE reserves the right to modify its product contents and technical data without prior notice. This document is property of SAMEC MACCHINE in Vicenza, Italy.


Italian Technology Quality



Some details

TECHNICAL SPECIFICATIONS

Reel External Diameter Max	500 -1000 mm (19.6in x 39in) Optional 1200mm or 47in max
Reel Weight	350 kg (772lbs)
Reel Width	650mm maximum (25.6in)
Multi-Conductor Cable Diameter	18mm (0.71in) max (Optional 25mm or 1in)
Flat Cable Width	18mm (0.71in) max
Reel Arbor Hole	65mm - 90mm (2.5in - 3.5in)
De-Reeling Speed	2 mt./sec.
Power Supply	230V 50/60Hz 3 Phase 7A
Air Supply	6 Bar Max
Overall Dimension	1700L x 1600W x 1720H mm (67in x 63in x 68in)
Weight	500kg (1102lbs)



Inline assembly example:
1 Motorized dereeler
2 Cut, strip & unjacket machine

ACCESSORIES INCLUDED

The machine is delivered with the following accessories:

- Reel rod kit
- Reel rods and centering cones for reels with holes with diameter = 65 mm – 90 mm

ACCESSORIES AVAILABLE UPON REQUEST

- Special reel rods with personalized centering cones
- Group H pulleys with special dimensions
- Non-motorized dancer

EN / 10-2018 / Rev. 00

SAMEC MACCHINE reserves the right to modify its product contents and technical data without prior notice. This document is property of SAMEC MACCHINE in Vicenza, Italy.

Italian Technology Quality



KM USA LLC
6479 N M-66
Charlevoix, MI 49720

PH: (231) 237-9060
www.kmusallc.com
sales@kmcrimp.com

